

LIGHT HEADS | Gemini Series




CL-Gemini65


CL-Gemini65-D9

CL-Gemini65-ULS


STANDARD



STANDARD CURVY



ULTRA SLIM




POWER	CRI	SDCM	CCT	BEAM	LUMINOUS FLUX
16W	> 90 > 80	< 3	3000K 2700K 4000K	24°	1333Lm

■ Sandy Black □ Sandy White

LIGHT DISTRIBUTION


3000K 90Ra

15°




h(m)	E(lx)	Φ(m)
1	12088	Φ0.27
2	3022	Φ0.56
3	1343	Φ0.82
4	755	Φ1.10
5	483	Φ1.37

24°




h(m)	E(lx)	Φ(m)
1	6470	Φ0.44
2	1617	Φ0.88
3	718	Φ1.33
4	404	Φ1.77
5	258	Φ2.22

36°



h(m)	E(lx)	Φ(m)
1	3107	Φ0.63
2	776	Φ1.27
3	345	Φ1.91
4	194	Φ2.55
5	124	Φ3.19

50°



h(m)	E(lx)	Φ(m)
1	1823	Φ0.91
2	455	Φ1.82
3	202	Φ2.74
4	114	Φ3.65
5	72	Φ4.56

cano light