



Low Bay DLC Premium Listed



Product Code	Input Voltage	Power	Lumen	CCT	Panel Size
CL-PL-1x4-36-3CCT-PA	120-347 VAC	Adjustable 20W-30W-40W	5000 lm	3CCT Adjustable	1x4 ft
CL-PL-2x2-40-3CCT-PA	120-347 VAC	Adjustable 20W-30W-40W	5000 lm	3500K 4000K	2x2 ft
CL-PL-2x4-50-3CCT-PA	120-347 VAC	Adjustable 30W-40W-50W	6250 lm	5000K	2x4 ft
CL-PL2-1x4-40-5CCT-PA5	120-347VAC	Adjustable 20W-25W-30W	125lm/W	5CCT Adjustable 3000K	1x4 ft
CL-PL2-2x2-40-5CCT-PA5	120-347VAC	45W-40W	125lm/W	3500K 4000K	2x2 ft
CL-PL2-2x4-50-5CCT-PA5	120-347VAC	Adjustable 30W-35W-40W-45W-50W	125lm/W	5000K 6500K	2x4 ft

Surface mount accessories are available.

- Backlit, uniform light with longer lifetime
- Galvanized Steel housing
- PMMA lens, No-yellowish outlook
- Dimmable 0-10V
- No flicker
- IP 20
- CRI >80
- PF >0.90
- Beam Angle: 120°
- Lifetime >50,000 hrs
- cETL approved (5CCT Series)
- cUL approved (3CCT Series)
- 5-Year Warranty

